
04 - Making a Cut

04 - Making a Cut



Step 1 — Setup



- Check that the table angle locking knobs and blade guide locking knob are securely tightened.
- Inspect the blade guides to ensure that nothing is loose or allows too much play.
- Λ


Don't ever use bandsaw without guards on it. If you see the bandsaw is missing a guard, contact a volunteer right away, and do not attempt to use the bandsaw. Before using the bandsaw, adjust the guard so that it is less than a fingertip's width above your piece to prevent your finger from passing through the saw.




Hook up a shop vac and turn on dust collection. Dust can accumulate in and around the wheel where the bandsaw rotates and can prevent it from rotating smoothly.

04 - Making a Cut

Step 2 — Press the start button





- Make sure a push stick is next to you.
- Position self and piece directly behind blade.
- Press the start button to turn on the saw.
- Wait for the saw to come up to speed before continuing.

Step 3 — Feed your material



This document was generated on 2023-03-02 07:13:47 AM (MST).

- Feed your material through the saw, following your marks.
 - Do NOT cut round objects on the bandsaw without consulting an area manager.

 Round objects can rotate and spin and get stuck on the saw blade.
- Key Point: Do not force your material through the saw blade. Check to see that the blade is sharp if the material doesn't feed through easily.
- Once the piece reaches, or is near, the red circle on the table, grab your push stick and proceed to finish your cut.

04 - Making a Cut

Step 4 — Press the stop button



- Press the stop button to turn off the saw.
- Key Point: Be sure to sweep and dispose of saw dust, and return the table to zero degrees (if tilted) when done.